


iDISPLAY™ Tablet 8"

UIT408



The iDISPLAY Tablet 8" is designed as an interactive display for any location. Operating on an Android operating system and powered by Pulse technology, this slim and elegant display includes all of the solutions needed for commercial locations. Attach to any standard TV/monitor VESA bracket and simply turn on the power. It is a fully interactive commercial display that uses capacitive touch, built in WiFi and LAN, and a host of integrated features that work in either landscape or portrait format. With the option to expand to 3G services*, this is an amazing, interactive digital display that creates an engaging, memorable consumer experience.



*3G optional, pending carrier compatibility/availability.
For more information about iDISPLAY™ Tablets
please visit our website: www.outform.com/iDisplay-Tablets

Panel Information	Screen Size	8"
	Resolution	1280 x 800 Pixels
	Brightness	280 cd/m ²
	Contrast Ratio	900
	Aspect Ratio	16:10
	Active Area Size (WxH)	172.2 x 107.6mm
	Viewing Angle Touch	80°/80°(H), 80°/80°(V)
	Touch Technology	Capacitive G+G 5 point
Hardware and OS	CPU	RK3188, Cortex-A9, up to 1.6GHz Quad Core
	GPU	Mali 400 MP4, 600MHz
	Internal Memory	1GB, DDR3
	Flash Memory	8GB
	Operating System	Android 4.4 / 5.1
	Battery	No Battery (Standard)
Video/Images	Video Formats	3GP, MP4, AVI, MKV, FLV, MOV
	Video Codecs	MPG-1, MPG-2, MPG-4, H.263, H.264, VC-1, RV, VP6/VP8, MVC
	Image Formats	JPG/JPEG, PNG, BMP
	HDMI Output	Mini HDMI
	Playback Software	Built-in software allows for easy setup of a playlist of videos and/or stills which can be looped infinitely without any additional software. Alternatively, any installed app can be auto-started upon boot-up.
Audio	Speakers	1W x 2
	Audio Codecs	MP3, WMA, AAC, FLAC, WAV
Communications	Bluetooth	4.0
	Wi-Fi	802.11 b/g/n 2.4GHz
	Wired Ethernet	100M/1000M, RJ45
	Wireless 3G	Through internal Mini-PCIE Card (Optional)
General information	Color	Black
	Camera	No Camera (Standard), 5MP (Optional)
	I/O ports	DC, Mini HDMI, 3.5mm Audio Output Jack, USB 2.0 Host x 2, Micro USB 2.0 OTG x 1, RJ45
	Included in Box	Display Unit, Power Adapter, VESA 75mm to 100mm Bracket, Power Cable, User Manual, Warranty
	Optional Accessories	Floor stand, counter stand (L), shelf clip, adjustable shelf clip, wall bracket, rotating bracket
	Sensors	G-Sensor (3-Axis accelerometer)
	Power Input	12V/2A
	Power Consumption	15W (max)
	Power Over Ethernet	Through RJ45
	Operating Temperature	0-40 °C
	Relative Humidity	85%
	Certifications	Display Unit: ROHS, FCC and CE complaint Power Supply Unit: UL, FCC and CE compliant Battery: UL, UN38.3
Dimensions	Size (L x W x H)	212 x 147 x 30mm
	Product Weight	0.55kg
	Gift Box Size	344 x 215 x 65mm
	Master Carton Size	360 x 285 x 235mm
	Master Carton Weight	5kg
	Units per Master Carton	4pcs