iDISPLAY™ Tablet 15.6" UIT215

WiFi™ 3G* 4G* LTE
BUILT FOR
COMMERCIAL USE

The iDISPLAY Tablet 15.6" is designed as an interactive counter display. Operating on an Android operating system and powered by Pulse technology, this slim and elegant display includes all of the solutions needed for commercial locations. Attach to any standard TV/monitor Vesa bracket - and just turn on the power. A fully interactive commercial display using capacitive touch (with built in WiFi and LAN) and a host of integrated features, in either landscape or portrait format. With the option to expand 3G/4G and GPS services with a USB dongle* (inserted in the secure back cover), this is a large screen interactive digital display for an engaging consumer experience.

405.2mm
15.95"

40.7mm
1.6"

VESA
100mm

254.5mm
10.01"

*3G/4G/GPS Optional, Pending carrier compatibility/availability.
For more information about iDISPLAY Tablets please
visit our website: **www.outform.com/idisplay**

OUTFORM™

Panel Information	Screen Size	15.6″
	LCD Brand	LG, LP156WF2
	Resolution	1920 x 1080
	Brightness	250 cd/m2
	Contrast Ratio	400
	Aspect Ratio	16:9
	Active Area size(HxV)	344.232 x 193.536
	Viewing Angle	65°/65°/55°/55°
	Touch Technology	Capacitive G+G 10 point
Hardware and OS	CPU	RK3188, Quad-core, 1.6G
	Graphics Hardware	3D Graphics
	Internal Memory(RAM)	1GB
	Flash Memory	8GB
	Operating System	Android 4.2
	Battery	N/A
Video/Images	Supported Formats	MPG-1;MPG-2;MPG-4;H.263;H.264;VC-1;RV;VP6/VP8;MVC;JPEG
	HDMI Output	N/A
Audio	Speakers	2 x 3W
	Audio Codecs	Supports: MP3, WMA, AAC, FLAC etc
Communications	Bluetooth	Supports Bluetooth 3.0
	Wi-Fi	Wi-Fi 802.11b/g/n
	Wired Ethernet	RJ45, 10M/100M
	GPS	Supports GPS dongle ext (Optional)
	Wireless 3G/4G	Supports USB Dongle (Optional)
General information	Color	Black/White
	Camera	2.0MP Front
	I/O ports	DC in: 12V 3A, Earphone x1, RJ45 x1, USB2.0: HOST x1, USB2.0: Device x1
	Accessories	Adapter, User manual, Power cable
	Sensors	3-Axis Sensor
	Power Supply	12V/3A
	Power Consumption	<25W
	Operation Temperature	0-40 centigrade
	Relative Humidity	0.85
	Certifications	ROHS, CE/FCC,PSU with UL
Dimensions	Size (W x D x H)	405 x 254 x 36mm
	NET Weight	2.72Kg
	Product Carton Size	628 x 308 x 89mm
	Master Carton Size	646 x 196 x 330mm
	Master Carton Weight	7.92Kg
	Units per Master Carton	2pcs/Carton